



SINGLE CLIPS (LSZH COATED)



Product Information

Fixing Clip/Saddle	Copper
Coating	TGIC Free Polyester Powder Coating
Material Properties	Halogen Free
Max. Working Temperature	200°C
Material Characteristics	Excellent Resistance to Corrosion Improved Resistance to Wear And Abrasion Good Impact Resistance Flexibility Compatibility with Food Products Good Hygienic Properties Long Service Life



P clip Reference WRCHL	Approximate Diameters of cables mm (Reference A)	Fixing Hole mm (Reference B)	Wood Screw Number	Suitable for the following LSZH Served OR CCM MICC Cables
26*	6.6 - 6.9	4	6	2L1, 1H2.5
28*	7.3 - 7.6	4	6	2L1.5, 3L1, 1H4
30*	7.7 - 8.0	5.25	8	3L1.5, 4L1, 1H6
32*	8.1 - 8.4	5.25	8	2L2.5
34*	8.7 - 9.0	5.25	8	3L2.5, 4L1.5, 1H10
37*	9.4 - 9.9	5.25	8	2L4, 4L2.5, 7L1, 1H16, 2H1.5, 3H1.5
40*	10.3 - 10.8	5.25	8	7L1.5, 2H2.5
43*	10.9 - 11.3	5.5	10	7L2.5, 1H25, 2H4, 3H2.5, 4H1.5
47*	12.4 - 12.8	5.5	10	1H35, 2H6, 3H4, 4H2.5, 7H1.5
51*	13.1 - 13.4	5.5	10	3H6, 4H4
54*	13.6 - 14.8	5.5	10	1H50, 2H10, 4H6, 7H2.5
59*	15.2 - 15.6	5.5	10	1H70, 3H10, 12H1.5
63*	16.4 - 16.8	5.5	10	2H16, 4H10
67*	16.9 - 17.3	7.1	14	1H95
71*	18.1 - 18.6	7.1	14	3H16, 12H2.5, 19H1.5
75*	19.2 - 19.6	7.1	14	1H120, 2H25, 3H25, 4H16
79*	20.0 - 21.4	7.1	14	1H150
88*	22.9 - 22.5	7.1	14	1H185, 4H25
101*	25.8 - 26.2	7	14	1H240



* Standard Colour e.g. RD = RED, OE = ORANGE, BK = Black, WE = White

TWO WAY SADDLES (LSZH COATED)



Product Information

Fixing Clip/Saddle	Copper
Coating	TGIC Free Polyester Powder Coating
Material Properties	Halogen Free
Max. Working Temperature	200°C
Material Characteristics	Excellent Resistance to Corrosion Improved Resistance to Wear And Abrasion Good Impact Resistance Flexibility Compatibility with Food Products Good Hygienic Properties Long Service Life



Saddle Reference WRSFL	Approximate Diameters of cables mm (Reference A)	Hole Size mm (Reference B)	Fixing Centre mm (Reference C)	Wood Screw Number	Suitable for the following LSZH Served OR CCM MICC Cables
272*	2 x 6.8 - 7.2	4.0	27.0	6	2L1, 1H2.5, 1H4
302*	2 x 7.6 - 8.0	4.0	27.0	6	2L1.5, 3L1
342*	2 x 8.6 - 9.0	5.25	36.0	8	2L2.5, 3L1.5, 3L2.5, 4L1.5, 1H6, 1H10
382*	2 x 9.6 - 10.1	5.25	36.0	8	2L4, 7L1, 2H1.5
422*	2 x 10.6 - 11.1	5.25	36.0	8	4L2.5, 7L1.5, 1H16, 2H2.5, 3H1.5
462*	2 x 11.6 - 12.1	5.5	49.0	10	7L2.5, 1H25, 2H4, 3H2.5, 4H1.5, 4H2.5
502*	2 x 12.4 - 13.3	5.5	49.0	10	1H35, 2H6, 3H4, 7H1.5
542*	2 x 13.4 - 14.3	5.5	49.0	10	1H50, 3H6, 4H4, 7H2.5
592*	2 x 14.4 - 15.3	5.5	49.0	10	2H10, 4H6
632*	2 x 15.4 - 17.2	5.5	49.0	10	1H70, 3H10, 12H1.5
702*	2 x 17.3 - 18.2	7.1	62.0	10	1H95, 2H16, 4H10
752*	2 x 18.3 - 20.1	7.1	62.0	14	1H120, 2H25, 3H16, 4H16, 12H2.5, 19H1.5
812*	2 x 20.2 - 21.0	7.1	62.0	14	1H150, 3H25
932*	2 x 22.7 - 23.2	7.1	73.0	14	1H185, 4H25
1042*	2 x 25.6 - 26.1	7.1	73.0	14	1H240

* Standard Colour e.g. RD = RED, OE = ORANGE, BK = Black, WE = White