

WMC Zero Halogen Shrouds - WRHGMM



NOTES:

WMC shrouds are manufactured from a Low Smoke Zero Halogen material and are used during installation to cover the cable glands giving a neat professional finish and can provide protection against dirt or foreign substances gathering on cable gland assembly.

The WMC Zero Halogen shroud comes in various sizes and colours and are supplied in packs of 10 for 20mm and packs of 2 for 25, 32 & 40mm

Gland Size	Description	WMC Product Number	Pack Quantity	Hole sizes	Min Wall
20mm	Low Smoke Zero Halogen Shroud	WRHGMM20/*	10	21.5mm	1.0mm
25mm		WRHGMM25/*	2	27.2mm	1.0mm
32mm		WRHGMM32/*	2	35.5mm	1.0mm
40mm		WRHGMM40/*	2	45.0mm	1.0mm

* Colour e.g. RD = RED, OE = ORANGE, BK = Black, WE = White

Grade	Halogen Free
Colour	Black, Red, Orange & White **
Hardness (IRHD)	65 m- 70 Shore A
Tensile Strength Mpa	7 Min
Tear Strength	23 n/m
Elongation @ Break %	400 Min
High Temp use (Con)	+250c
High Temp use (Peak)	+275c
Low Temp Flexibility	-60c
Oxygen Index	32
Smoke Evolution	Low Smoke Ao<0. 029
Oil Resistant	Fair
Dielectric Strength	High
Ozone Resistance	Excellent
Halogen Content	<0. 5

** Other colours available on request